

ISO 3008-3:2016-05 (E)

Fire resistance tests - Part 3: Door and shutter assemblies horizontally oriented

Contents	Page
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test equipment	2
5 Test conditions	2
6 Test specimen	2
6.1 Size of specimen	2
6.2 Design of specimen	2
6.3 Verification	3
7 Installation of test specimen	3
7.1 General	3
7.2 Supporting construction	3
7.3 Test construction	3
7.3.1 Associated and supporting construction	3
7.3.2 Associated construction	4
7.3.3 Supporting construction	4
7.4 Gaps	4
8 Conditioning	4
8.1 Moisture content	4
8.2 Mechanical	4
9 Application of instrumentation	4
9.1 Temperature measurements	4
9.1.1 Furnace temperature measuring instrument	4
9.1.2 Unexposed face thermocouples	5
9.2 Maximum temperature	6
9.3 Pressure measurements	6
9.4 Heat flux measurement	6
9.4.1 General	6
9.4.2 Apparatus	7
9.4.3 Procedure	7
9.4.4 Measurement	8
9.5 Loading	8
9.6 Deflection	8
10 Test procedure	8
10.1 Gap measurements	9
10.2 Test Measurements	9
11 Performance criteria	9
11.1 Integrity	9

11.2	Insulation	9
11.3	Loadbearing capacity	9
12	Test report	10
13	Field of direct application of test results	10
13.1	General	10
13.2	Timber constructions	11
13.3	Steel constructions	11
13.4	Glazed constructions	11
13.5	Fixings/hardware	11
Annex A (normative) Conditioning requirements for supporting constructions		13
Annex B (informative) Estimation of radiant heat flux using measured surface temperature and Stefan-Boltzmann law		14