

DIN EN 1993-4-1:2017-09 (E)

Eurocode 3: Design of steel structures - Part 4-1: Silos

Contents

| | |
|--|-----------|
| European foreword | 4 |
| European foreword to Amendment 1 | 8 |
| 1 General | 9 |
| 1.1 Scope | 9 |
| 1.2 Normative references | 9 |
| 1.3 Assumptions | 10 |
| 1.4 Distinction between principles and application rules | 10 |
| 1.5 Terms and definitions | 10 |
| 1.6 Symbols used in Part 4.1 of Eurocode 3 | 13 |
| 1.7 Sign conventions | 15 |
| 1.8 Units | 20 |
| 2 Basis of design | 21 |
| 2.1 Requirements | 21 |
| 2.2 Reliability differentiation | 21 |
| 2.3 Limit states | 22 |
| 2.4 Actions and environmental effects | 23 |
| 2.5 Material properties | 23 |
| 2.6 Geometrical data | 23 |
| 2.7 Modelling of the silo for determining action effects | 23 |
| 2.8 Design assisted by testing | 23 |
| 2.9 Action effects for limit state verifications | 24 |
| 2.10 Durability | 25 |
| 2.11 Fire resistance | 25 |
| 3 Properties of materials | 26 |
| 3.1 General | 26 |
| 3.2 Structural steels | 26 |
| 3.3 Stainless steels | 26 |
| 3.4 Special alloy steels | 26 |
| 3.5 Toughness requirements | 27 |
| 4 Basis for structural analysis | 28 |
| 4.1 Ultimate limit states | 28 |
| 4.2 Analysis of the structure of a shell silo | 29 |
| 4.3 Analysis of the box structure of a rectangular silo | 32 |
| 4.4 Equivalent orthotropic properties of corrugated sheeting | 33 |
| 5 Design of cylindrical walls | 36 |
| 5.1 Basis | 36 |
| 5.2 Distinctions between cylindrical shell forms | 36 |
| 5.3 Resistance of silo cylindrical walls | 37 |
| 5.4 Special support conditions for cylindrical walls | 64 |
| 5.5 Detailing for openings in cylindrical walls | 69 |
| 5.6 Serviceability limit states | 70 |

| | | |
|----------|--|------------|
| 6 | Design of conical hoppers | 71 |
| 6.1 | Basis | 71 |
| 6.2 | Distinctions between hopper shell forms | 71 |
| 6.3 | Resistance of conical hoppers | 72 |
| 6.4 | Considerations for special hopper structures | 77 |
| 6.5 | Serviceability limit states | 79 |
| 7 | Design of circular conical roof structures | 80 |
| 7.1 | Basis | 80 |
| 7.2 | Distinctions between roof structural forms | 80 |
| 7.3 | Resistance of circular conical silo roofs | 80 |
| 8 | Design of transition junctions and supporting ring girders | 82 |
| 8.1 | Basis | 82 |
| 8.2 | Analysis of the junction | 80 |
| 8.3 | Structural resistances | 92 |
| 8.4 | Limit state verifications | 96 |
| 8.5 | Considerations concerning support arrangements for the junction | 98 |
| 9 | Design of rectangular and planar-sided silos | 100 |
| 9.1 | Basis | 100 |
| 9.2 | Classification of structural forms | 100 |
| 9.3 | Resistance of unstiffened vertical walls | 101 |
| 9.4 | Resistance of silo walls composed of stiffened and corrugated plates | 101 |
| 9.5 | Silos with internal ties | 100 |
| 9.6 | Strength of pyramidal hoppers | 106 |
| 9.7 | Vertical stiffeners on box walls | 108 |
| 9.8 | Serviceability limit states | 108 |
| | Annex A: [Informative] | 110 |
| | Simplified rules for circular silos in Consequence Class 1 | 110 |
| | A.1 Action combinations for Consequence Class 1 | 110 |
| | A.2 Action effect assessment | 110 |
| | A.3 Ultimate limit state assessment | 110 |
| | Annex B: [Informative] | 117 |
| | Expressions for membrane stresses in conical hoppers | 117 |
| | Annex C: [Informative] | 119 |
| | Distribution of wind pressure around circular silo structures | 119 |