

DIN 16873:2018-09 (E)

Pipes and fittings of unplasticized poly(vinyl chloride) (PVC-U) for cable ducting - Dimensions and technical delivery conditions

Contents	Page
Foreword	4
1 Scope	5
2 Normative references	5
3 Terms and definitions.....	6
4 Symbols and abbreviations.....	7
4.1 Symbols	7
4.2 Abbreviations	7
5 Dimensions, designation.....	8
5.1 General	8
5.2 Pipes	8
5.2.1 General	8
5.2.2 Pipe outside diameters and wall thicknesses	8
5.3 Fittings.....	10
6 Material	10
6.1 Pipes and fittings.....	10
6.2 Seals.....	10
6.3 Adhesives	10
7 Requirements	10
7.1 General	10
7.2 Appearance	10
7.3 Colour.....	11
7.4 Dimensions and tolerances.....	11
7.5 Strength properties	11
7.5.1 Long-term hydrostatic strength	11
7.5.2 Resistance to external blows	11
7.6 Heat reversion.....	12
7.7 Vicat softening temperature.....	12
8 Testing	12
8.1 Appearance	12
8.2 Colour.....	12
8.3 Dimensions.....	12
8.4 Strength properties	13
8.4.1 Long-term hydrostatic strength	13
8.4.2 Resistance to external blows	13
8.5 Heat reversion.....	13
8.6 Vicat softening temperature.....	13
9 Marking	13
9.1 General	13
9.2 Minimum marking of pipes.....	14
10 Laying instructions	14
10.1 Structural strength	14

10.2	Installation of pipes and fittings.....	14
Annex A	(normative) Fittings for straight pipes	15
A.1	Dimensions.....	15
A.2	Requirements	20
A.3	Testing of injection-moulded fittings.....	21
A.4	Additional marking.....	21
Annex B	(informative) Terms which are not used in this standard, but are of relevance for the	
	user	22
Bibliography		23