

ISO 4642-2:2009-02 (E)

Rubber and plastics hoses, non-collapsible, for fire-fighting service - Part 2: Semi-rigid hoses (and hose assemblies) for pumps and vehicles

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Classification	2
4.1 General	2
4.2 Classification by types (hose construction)	2
4.3 Classification by class (materials for lining and cover)	3
4.4 Classification by category	3
5 Dimensions, tolerances and maximum mass	3
5.1 Inside diameter and maximum mass	3
5.2 Length and tolerances on length	4
5.3 Concentricity	4
6 Performance requirements of finished hose	4
6.1 Hydrostatic requirements	4
6.2 Adhesion	5
6.3 Accelerated ageing	5
6.4 Abrasion resistance	5
6.5 Low temperature flexibility	6
6.6 Hot surface resistance	6
6.7 Ozone resistance	6
6.8 Bending and crush resistance	6
6.9 UV resistance (xenon arc lamp)	6
6.10 Loss in mass on heating	6
6.11 Deformation under crushing (type C only)	6
6.12 Hose assemblies	7
7 Frequency of testing	7
8 Type tests	7
9 Test report	7
10 Recommendation for packaging and storage	7
11 Marking	8
Annex A (normative) Kink pressure test	9
Annex B (normative) Accelerated ageing test	10
Annex C (normative) Surface abrasion resistance test	11
Annex D (normative) Point abrasion resistance test	13

Annex E (normative) Hot surface resistance test	16
Annex F (normative) Bending and crush resistance test	21
Annex G (normative) Deformation under crushing test	23
Annex H (normative) Test for hose assemblies	25
Annex I (normative) Type test and routine test	26
Annex J (informative) Production tests	27
Bibliography	28