

DIN EN 15542:2008-06 (E)

Ductile iron pipes, fittings and accessories - External cement mortar coating for pipes - Requirements and test methods

Contents	Page
Foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	7
4 Ordering information	8
5 Technical requirements	8
5.1 Zinc coating	8
5.2 Primer film thickness	8
5.3 Fresh cement mortar composition	8
5.4 Fresh cement mortar layer thickness	9
5.5 Pipe ends	9
5.6 Appearance of cured cement mortar coating	9
5.7 Thickness of cured cement mortar coating	9
5.8 Repairs	10
5.9 Marking	10
6 Performance requirements	10
6.1 Cement mortar Constituents	10
6.1.1 Cement	10
6.1.2 Sand	10
6.1.3 Fibres	10
6.1.4 Surface tissue	10
6.1.5 Organic components	11
6.2 Bond strength	11
6.3 Impact resistance	11
7 Test methods	11
7.1 Routine tests	11
7.1.1 Zinc coating	11
7.1.2 Primer	11
7.1.3 Fresh cement mortar composition	11
7.1.4 Thickness of the cement mortar layer	11
7.1.5 Pipe ends	11
7.1.6 Appearance and continuity of cured cement mortar coating	12
7.1.7 Thickness of the cured cement mortar coating	12
7.1.8 Repairs	12
7.1.9 Marking	12
7.2 Performance tests	12
7.2.1 Constituents	12
7.2.2 Bond strength	13
7.2.3 Impact strength	13
Annex A (informative) Quality assurance	14

A.1	General	14
A.2	Performance test	15
A.3	Quality assessment system	16
Annex B (informative) Application process		17
B.1	Coating process	17
B.1.1	Temperature during work	17
B.1.2	Application of zinc coating	17
B.1.3	Application of primer	17
B.2	Application of cement mortar	17
B.2.1	Application with primer	17
B.2.2	Application without primer	17
Annex C (informative) Explanatory notes		18
Annex D (informative) Calculation of fresh cement mortar composition		19
D.1	General	19
D.2	Sampling	19
D.3	Determination of the content of sand and fibres	19
D.4	Determination of the fibre content	20
Bibliography		21