

ISO 21072-3:2010-03 (E)

Ships and marine technology - Marine environment protection: performance testing of oil skimmers - Part 3: High viscosity oil

Contents	Page
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Test facility requirements	2
4.1 General	2
4.2 Oil properties	2
4.3 Air and water temperature	3
4.4 Oil slick thickness	3
4.5 Measuring tanks	3
5 Clearance requirements	3
6 Test parameters	3
6.1 General	3
6.2 Test oil properties	3
6.3 Oil slick thickness	4
6.4 Skimmer operating parameters	4
6.5 Debris interference	4
6.6 Skimmer movement through slick	5
7 Test procedures	5
7.1 Preparations prior to testing	5
7.2 Actions during testing period	6
7.3 Actions after testing	6
8 Performance parameters	6
8.1 General	6
8.2 Fluid recovery rate	6
8.3 Oil recovery testing rate	7
8.4 Oil recovery efficiency	7
9 Measurements and reporting	7
9.1 General	7
9.2 Oil properties	7
9.3 Environmental parameters	7
9.4 Skimmer operating parameters	7
9.5 Other test parameters	8
9.6 Recovery parameters	8
9.7 Performance parameters (calculated parameters)	8
9.8 Equipment specification and test documentation	8
10 Quality control	8
10.1 Test duration and fluid volume	8
10.2 Repetitions	9
Bibliography	10