

# DIN EN 14034-2:2011-04 (E)

Determination of explosion characteristics of dust clouds - Part 2: Determination of the maximum rate of explosion pressure rise  $(dp/dt)_{max}$  of dust clouds (includes Amendment A1:2011)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		4
Introduction .....		5
1	Scope .....	6
2	Normative references .....	6
3	Terms and definitions .....	6
4	Test apparatus .....	7
4.1	General .....	7
4.2	Explosion vessel .....	8
4.3	Dust dispersion system (dust container, fast acting valve, connecting tube, dust disperser) .....	10
4.4	Ignition source .....	13
4.5	Control unit .....	13
4.6	Pressure measuring system .....	13
5	Dust sample .....	13
6	Test procedure .....	13
7	Calibration and verification .....	16
7.1	Calibration .....	16
7.2	Verification .....	16
8	Safety precautions / instructions .....	17
9	Alternative test equipment / procedures .....	17
10	Test report .....	18
Annex A (normative) Electro Pneumatic Valve .....		19
Annex B (normative) Dust dispenser with 5 mm holes .....		22
Annex C (normative) 20 l sphere .....		25
C.1	General .....	25
C.2	Test apparatus .....	25
C.3	Test conditions .....	26
C.4	Test procedure .....	26
C.5	Calculation of $(dp/dt)_{max}$ , 20 l, $K_{max}$ and $K_{St}$ .....	27
Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC .....		28
Bibliography .....		29

<b>Figures</b>		
<b>Figure 1</b>	<b>-- 1 m<sup>3</sup> vessel (schematic)</b>	<b>9</b>
<b>Figure 2</b>	<b>-- Dust container with blasting cap activated valve as commonly used for explosion suppression (schematic; it is commercially available)</b>	<b>10</b>
<b>Figure 3</b>	<b>-- Location of the 6 mm holes in the dust disperser</b>	<b>12</b>
<b>Figure 4</b>	<b>-- Dust dispersion and pressure-time curve</b>	<b>15</b>
<b>Figure 5</b>	<b>-- Determination of the maximum rate of explosion pressure rise (dp/dt)<sub>max</sub></b>	<b>16</b>
<b>Figure A.1</b>	<b>-- Electro Pneumatic Valve (schematic)</b>	<b>20</b>
<b>Figure A.2</b>	<b>-- Discharge characteristic of dust dispersers (without dust)</b>	<b>21</b>
<b>Figure B.1</b>	<b>-- Location of the 5 mm holes in the dust disperser</b>	<b>23</b>
<b>Figure B.2</b>	<b>-- Rebound nozzle</b>	<b>24</b>
<b>Figure B.3</b>	<b>-- Dispersion cup</b>	<b>24</b>
<b>Figure C.1</b>	<b>-- Test equipment 20 l sphere (schematic)</b>	<b>26</b>
<b>Tables</b>		
<b>Table 1</b>	<b>-- Maximum permissible deviations SEQ</b>	<b>17</b>