ISO 16332:2018 (E)

Diesel engines — Fuel filters — Method for evaluating fuel/water separation efficiency

Contents

Foreword

Introduction

- 1 Scope
- 2 Normative references
- 3 Terms and definitions
- 4 Symbols

5 Test equipment

- 5.1 Test fluids
- 5.1.1 Test fuels
- 5.1.2 Test water
- 5.2 Laboratory equipment
- 5.2.1 General
- 5.2.2 Sampling bottles and glassware
- 5.2.3 Water detection system
- 5.2.3.1 Karl Fischer (KF) titrator
- 5.2.3.2 Centrifuge
- 5.2.4 Equipment for determination of IFT
- 5.3 Test stand
- 5.3.1 General
- 5.3.2 Fuel/water separator test circuit
- 5.3.2.1 Fuel sump (1)
- 5.3.2.2 Water sump (6)
- 5.3.2.3 Heat exchanger (3)
- 5.3.2.4 Test pump (2)
- 5.3.2.5 Water injection pump (7)
- 5.3.2.6 Fuel flow meter (5a)
- 5.3.2.7 Water flow meter (5b)
- 5.3.2.8 Injection device (8)
- 5.3.2.9 Water emulsifying device (9) 5.3.2.10 Operating pressure gauge (10
- 5.3.2.10 Operating pressure gauge (10) 5.3.2.11 Differential pressure gauges (11)
- 5.3.2.11 Differential pressure gauges (11) 5.3.2.12 Upstream sampling point (12)
- 5.3.2.12 Upstream sampling point (1) 5.3.2.13 Temperature indicator (13)
- 5.3.2.13 Temperature Indicator (13) 5.3.2.14 Water drainage system (15)
- 5.3.2.14 Water trainage system (13 5.3.2.15 Back pressure gauge (16)
- 5.3.2.16 Back pressure control valve (17) (optional equipment)
- 5.3.2.17 Downstream sampling point (18)
- 5.3.2.18 Clean-up system (19)
- 5.3.2.19 Droplet size distribution measurement device (20)
- 5.3.2.20 Bypass line (21)
- 5.3.2.21 Inline water concentration measurement device (22) (Optional equipment)
- 5.3.2.22 General requirements on the hydraulic piping system
- 6 Test conditions
 - 6.1 Volume of test fuel VT
 - 6.2 Test fuel temperature T
 - 6.3 Test flow rate QT

- 6.4 Upstream undissolved water concentration cU,up
- 6.4.1 General
- 6.4.2 Water injection flow rate QW
- 6.5 Back pressure
- 6.6 Sampling
- 6.7 Droplet size distribution DSD
- 6.8 Test duration ttest
- 7 Accuracy of measuring instruments and test conditions
- 8 Validation procedures
 - 8.1 General
 - 8.2 Water detection system
 - 8.2.1 Inline water concentration measurement device (optional)
 - 8.2.2 Karl Fischer titration sytem
 - 8.3 Emulsifying device
 - 8.4 Filter test circuit and water injection system
 - 8.4.1 General
 - 8.4.2 Validation preparation
 - 8.4.3 Preconditioning cycle
 - 8.4.4 Validation cycle
- 9 Simplified laboratory test
 - 9.1 Test procedure
 - 9.1.1 General
 - 9.1.2 Pre-test preparation
 - 9.1.3 Preconditioning cycle
 - 9.1.4 Efficiency measurement
 - 9.2 Calculation of water separation efficiency and reporting of test results
- 10 Test report
- Annex A (normative) Fuel treatment to obtain test fuel F2
- Annex B (normative) Water emulsifying device
 - B.1 Calibrated orifice design details
 - B.2 Calibrated orifices concept
 - B.3 DSD generated by orifices
 - B.4 Water emulsifying device calibration procedure
- Annex C (normative) Conditions and parameters for the determination of the interfacial tension according to ISO 9101, drop volume method
- Annex D (normative) Validation of the sampling procedure for Karl Fischer titration and centrifuge
 - D.1 Karl Fischer titration (manual sampling)
 - D.1.1 Primary sampling procedure
 - D.1.2 Secondary sampling procedure
 - D.1.3 Secondary sampling procedure validation
 - D.2 Karl Fischer titration (automated sampling)
 - D.3 Centrifuge
- Annex E (normative) Determination of the concentration cS of dissolved water in saturated fuel
- Annex F (informative) Typical fuel/water separator test report
- Annex G (informative) Report round robin
- Annex H (informative) Effect of KF-titration on the precision of water separation efficiency measurements

Page count: 44