

# DIN EN 12831-1:2017-09 (E)

## Energy performance of buildings - Method for calculation of the design heat load - Part 1: Space heating load, Module M3-3

---

| Contents                                                                                               | Page |
|--------------------------------------------------------------------------------------------------------|------|
| European foreword .....                                                                                | 5    |
| Introduction .....                                                                                     | 6    |
| 1 Scope .....                                                                                          | 8    |
| 2 Normative references .....                                                                           | 12   |
| 3 Terms and definitions .....                                                                          | 12   |
| 4 Symbols and abbreviations .....                                                                      | 15   |
| 4.1 Symbols .....                                                                                      | 15   |
| 4.2 Subscripts .....                                                                                   | 16   |
| 5 Description of the methods .....                                                                     | 19   |
| 6 Standard method - Heat load of rooms, building entities and buildings .....                          | 20   |
| 6.1 Output data .....                                                                                  | 20   |
| 6.2 Input data .....                                                                                   | 21   |
| 6.3 Calculation procedure .....                                                                        | 27   |
| 6.3.1 Design heat load .....                                                                           | 27   |
| 6.3.2 Design transmission heat losses of a heated space (i) .....                                      | 29   |
| 6.3.3 Design ventilation heat loss .....                                                               | 33   |
| 6.3.4 Additional heating-up power in intermittently heated spaces .....                                | 41   |
| 6.3.5 Time constant .....                                                                              | 42   |
| 6.3.6 Heat transfer coefficients without temperature adjustment .....                                  | 43   |
| 6.3.7 External design temperature (climatic data) .....                                                | 44   |
| 6.3.8 Influence of the heat emission system in high rooms (ceiling height 4 m) .....                   | 46   |
| 7 Simplified method for the calculation of the design heat load of a heated space (single rooms) ..... | 48   |
| 7.1 Output data .....                                                                                  | 48   |
| 7.2 Input data .....                                                                                   | 48   |
| 7.3 Calculation procedure .....                                                                        | 49   |
| 7.3.1 Design heat load of a heated space .....                                                         | 49   |
| 7.3.2 Design transmission heat loss of a heated space .....                                            | 50   |
| 7.3.3 Design ventilation heat loss of a heated space .....                                             | 50   |
| 8 Simplified method for the calculation of the building design heat load .....                         | 51   |
| 8.1 Output data .....                                                                                  | 51   |
| 8.2 Input data .....                                                                                   | 51   |
| 8.3 Calculation procedure .....                                                                        | 52   |
| 8.3.1 Building design heat load .....                                                                  | 52   |
| 8.3.2 Building design transmission heat loss .....                                                     | 53   |
| 8.3.3 Design ventilation heat loss of a building .....                                                 | 53   |
| 9 Compliance check .....                                                                               | 54   |
| 9.1 General .....                                                                                      | 54   |
| 9.2 Dimensioning of heat emission systems .....                                                        | 54   |
| 9.3 Dimensioning of heat generators .....                                                              | 54   |

|                                                                                                                          |           |
|--------------------------------------------------------------------------------------------------------------------------|-----------|
| <b>Annex A (normative) Input data, structure for default values .....</b>                                                | <b>55</b> |
| <b>A.1 General .....</b>                                                                                                 | <b>55</b> |
| <b>A.2 Input data for the standard method (6) .....</b>                                                                  | <b>55</b> |
| <b>A.2.1 Consideration of thermal bridges .....</b>                                                                      | <b>55</b> |
| <b>A.2.2 Correction of U-values for the influence of building element properties and meteorological conditions .....</b> | <b>55</b> |
| <b>A.2.3 Heat loss through the ground .....</b>                                                                          | <b>55</b> |
| <b>A.2.4 Temperature adjustment for heat loss to unheated spaces .....</b>                                               | <b>56</b> |
| <b>A.2.5 Internal temperatures of adjacent building entities .....</b>                                                   | <b>56</b> |
| <b>A.2.6 Influence of the heat emission system in high rooms .....</b>                                                   | <b>56</b> |
| <b>A.2.7 Specific thermal storage capacity <math>c_{eff}</math> .....</b>                                                | <b>57</b> |
| <b>A.2.8 Specific properties of air .....</b>                                                                            | <b>57</b> |
| <b>A.2.9 Volume flow ratio between room (i) and zone (z) .....</b>                                                       | <b>58</b> |
| <b>A.2.10 Air tightness .....</b>                                                                                        | <b>58</b> |
| <b>A.2.11 Minimum air change rate .....</b>                                                                              | <b>58</b> |
| <b>A.2.12 Coefficient for the volume flow ratio <math>f_{qv,z}</math> .....</b>                                          | <b>59</b> |
| <b>A.2.13 Estimation of design data of external ATDs .....</b>                                                           | <b>59</b> |
| <b>A.2.14 Pressure exponent for leakages .....</b>                                                                       | <b>59</b> |
| <b>A.2.15 Adjustment factor for the orientation of the zone (orientation factor) .....</b>                               | <b>59</b> |
| <b>A.2.16 Adjustment factor for the number of exposed facades .....</b>                                                  | <b>60</b> |
| <b>A.2.17 Air volume flow through large openings .....</b>                                                               | <b>60</b> |
| <b>A.2.18 Additional heating-up power in intermittently heated spaces <math>h_u</math> .....</b>                         | <b>60</b> |
| <b>A.2.19 Heat gains gain .....</b>                                                                                      | <b>60</b> |
| <b>A.3 Input data for the simplified methods (7, 8) .....</b>                                                            | <b>60</b> |
| <b>A.3.1 Ratio between external and internal surface areas .....</b>                                                     | <b>60</b> |
| <b>A.3.2 Thermal bridges .....</b>                                                                                       | <b>61</b> |
| <b>A.3.3 Temperature correction factor <math>f_x</math> .....</b>                                                        | <b>61</b> |
| <b>A.3.4 Air change rate .....</b>                                                                                       | <b>61</b> |
| <b>A.4 Input data for the standard method and the simplified methods .....</b>                                           | <b>61</b> |
| <b>A.4.1 Climatic data .....</b>                                                                                         | <b>61</b> |
| <b>A.4.2 Internal design temperature .....</b>                                                                           | <b>64</b> |
| <b>A.4.3 Simplified determination of U-Values .....</b>                                                                  | <b>64</b> |
| <b>Annex B (informative) Input data, default values .....</b>                                                            | <b>65</b> |
| <b>B.1 General .....</b>                                                                                                 | <b>65</b> |
| <b>B.2 Input data for the standard method (6) .....</b>                                                                  | <b>65</b> |
| <b>B.2.1 Consideration of thermal bridges .....</b>                                                                      | <b>65</b> |
| <b>B.2.2 Correction of U-values for the influence of building element properties and meteorological conditions .....</b> | <b>65</b> |
| <b>B.2.3 Heat loss through the ground .....</b>                                                                          | <b>65</b> |
| <b>B.2.4 Temperature adjustment for heat loss to unheated spaces .....</b>                                               | <b>66</b> |
| <b>B.2.5 Internal temperatures of adjacent building entities .....</b>                                                   | <b>66</b> |
| <b>B.2.6 Influence of the heat emission system in high rooms .....</b>                                                   | <b>66</b> |
| <b>B.2.7 Specific thermal storage capacity <math>c_{eff}</math> .....</b>                                                | <b>67</b> |
| <b>B.2.8 Specific properties of air .....</b>                                                                            | <b>68</b> |
| <b>B.2.9 Volume flow ratio between room (i) and zone (z) .....</b>                                                       | <b>68</b> |
| <b>B.2.10 Air tightness .....</b>                                                                                        | <b>68</b> |
| <b>B.2.11 Coefficient for the volume flow ratio <math>f_{qv,z}</math> .....</b>                                          | <b>69</b> |
| <b>B.2.12 Estimation of design data of external ATDs .....</b>                                                           | <b>70</b> |
| <b>B.2.13 Pressure exponent for leakages .....</b>                                                                       | <b>71</b> |
| <b>B.2.14 Adjustment factor for the orientation of the zone (orientation factor) .....</b>                               | <b>71</b> |
| <b>B.2.15 Adjustment factor for the number of exposed facades .....</b>                                                  | <b>71</b> |
| <b>B.2.16 Air volume flow through large openings .....</b>                                                               | <b>71</b> |
| <b>B.2.17 Additional heating-up power in intermittently heated spaces <math>h_u</math> .....</b>                         | <b>71</b> |
| <b>B.2.18 Heat gains gain .....</b>                                                                                      | <b>71</b> |
| <b>B.3 Input data for the simplified methods (7, 8) .....</b>                                                            | <b>71</b> |
| <b>B.3.1 Ratio between external and internal surface areas .....</b>                                                     | <b>71</b> |
| <b>B.3.2 Thermal bridges .....</b>                                                                                       | <b>72</b> |
| <b>B.3.3 Temperature correction factor <math>f_x</math> .....</b>                                                        | <b>72</b> |
| <b>B.3.4 Air change rate .....</b>                                                                                       | <b>72</b> |

|                                                                                                                                                              |                                                                                                                                        |           |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|-----------|
| <b>B.4</b>                                                                                                                                                   | <b>Input data for the standard method and the simplified methods .....</b>                                                             | <b>72</b> |
| <b>B.4.1</b>                                                                                                                                                 | <b>Climatic data .....</b>                                                                                                             | <b>72</b> |
| <b>B.4.2</b>                                                                                                                                                 | <b>Internal design temperature .....</b>                                                                                               | <b>73</b> |
| <b>B.4.3</b>                                                                                                                                                 | <b>Simplified determination of U-Values .....</b>                                                                                      | <b>74</b> |
| <b>Annex C (informative) Detailed consideration of thermal bridges .....</b>                                                                                 |                                                                                                                                        | <b>77</b> |
| <b>Annex D (informative) Internal temperatures <math>t_i</math> of adjacent building entities or adjacent unheated spaces within the same building .....</b> |                                                                                                                                        | <b>78</b> |
| <b>Annex E (informative) Equivalent thermal transmittance of building elements against ground .....</b>                                                      |                                                                                                                                        | <b>81</b> |
| <b>Annex F (informative) Estimation of heating-up power in intermittently heated spaces (6.3.4) .....</b>                                                    |                                                                                                                                        | <b>84</b> |
| <b>F.1</b>                                                                                                                                                   | <b>General .....</b>                                                                                                                   | <b>84</b> |
| <b>F.2</b>                                                                                                                                                   | <b>Determination of the specific heating-up power <math>h_{u,i}</math> based on the time of disuse .....</b>                           | <b>86</b> |
| <b>F.3</b>                                                                                                                                                   | <b>Determination of the specific heating-up power <math>h_{u,i}</math> based on the internal temperature drop during setback .....</b> | <b>87</b> |
| <b>Annex G (informative) External air volume flow through large openings .....</b>                                                                           |                                                                                                                                        | <b>89</b> |
| <b>Bibliography .....</b>                                                                                                                                    |                                                                                                                                        | <b>94</b> |