

DIN EN 13071-2:2008-10 (E)

Stationary waste containers up to 5 000 l, top lifted and bottom emptied - Part 2: Additional requirements for underground or partly underground systems

Contents	Page
Foreword	3
1 Scope	4
2 Normative references	4
3 Terms and definitions	5
4 Requirements	6
4.1 General requirements	6
4.2 Design	6
4.3 Safety requirements	7
4.3.1 Hole	7
4.3.2 Pedestrian platform	7
4.3.3 Safety floor	7
4.3.4 Safety barrier	7
5 Test conditions	7
6 Test procedures	8
6.1 Tests conducted on the container	8
6.2 Specific tests conducted on underground and partly underground systems	8
6.2.1 Resistance of the safety barrier	8
6.2.2 Resistance of the safety floor	8
6.2.3 Functionality of the safety floor and safety barrier	9
6.2.4 Resistance of the pedestrian platform	9
6.2.5 Resistance of the emergent part to exterior impacts	9
6.3 Corrosion	11
6.4 Weathering (for thermoplastics only)	11
6.4.1 Requirement	11
6.4.2 Procedure	11
6.5 Sequence of tests	11
7 Recommendations	12
8 Data sheet	12
9 Marking	12
10 Test report	12
Annex A (informative) A-deviations	13
Figures Figure 1 -- Underground and partly underground system	5
Figure 2 -- Example of resistance of emergent part to exterior impacts	10
Tables Table 1 -- Sequence of the tests	12