

# DIN EN ISO 11960:2021-08 (E)

Petroleum and natural gas industries - Steel pipes for use as casing or tubing for wells (ISO 11960:2020); English version EN ISO 11960:2021, only on CD-ROM

---

<b>Contents</b>		<b>Page</b>
<b>Foreword</b>		<b>x</b>
<b>Introduction</b>		<b>xi</b>
<b>1</b>	<b>Scope</b>	<b>1</b>
<b>2</b>	<b>Normative references</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviated terms</b>	<b>3</b>
3.1	Terms and definitions	3
3.2	Symbols and abbreviated terms	7
<b>4</b>	<b>Conformance</b>	<b>8</b>
4.1	Dual referencing of normative references	8
4.2	Units of measurement	9
<b>5</b>	<b>Information to be supplied by the purchaser</b>	<b>9</b>
5.1	Grades C90, T95 and C110	9
5.2	Casing	9
5.3	Tubing	11
5.4	Coupling stock, coupling material and accessory material	13
<b>6</b>	<b>Process of manufacture</b>	<b>14</b>
6.1	General	14
6.2	Heat treatment	14
6.2.1	General	14
6.2.2	Grades J55, K55, N80 all types and R95	15
6.2.3	Grades L80 all types, C90, T95 and C110	15
6.3	Straightening	15
6.3.1	Grades H40, J55, K55, N80 all types	15
6.3.2	Grades R95 and P110	15
6.3.3	Grade L80	15
6.3.4	Grades C90, T95 and C110	16
6.3.5	Grade Q125	16
6.4	Traceability	16
6.4.1	General	16
6.4.2	Serialization of Grades C90, T95, C110 and Q125	16
6.5	Processes requiring validation	16
<b>7</b>	<b>Material requirements</b>	<b>17</b>
7.1	Chemical composition	17
7.2	Tensile properties	17
7.2.1	General	17
7.2.2	Elongation	17
7.2.3	Yield strength	17
7.2.4	Statistical tensile testing — Grades C90, T95 and C110	18
7.3	Charpy V-notch test — General requirements	18
7.3.1	Evaluation of test results	18
7.3.2	Critical thickness	18
7.3.3	Specimen size and orientation	18
7.3.4	Hierarchy of test specimens	18
7.3.5	Alternative size impact test specimens	19
7.3.6	Sub-size test specimens	19
7.3.7	Test temperature	19
7.3.8	Statistical impact testing	19
7.3.9	Reference information	19
7.4	Charpy V-notch — Absorbed energy requirements for coupling stock, coupling material, coupling blanks and couplings	19
7.4.1	General	19
7.4.2	Grade H40	19

7.4.3	Grades J55 and K55 for API threads.....	19
7.4.4	Grades N80 all Types, R95, L80 all Types, C90, T95, P110 and Q125 for API threads.....	20
7.4.5	Special end-finish.....	20
7.5	Charpy V-notch — Absorbed energy requirements for pipe.....	20
7.5.1	Grades H40, J55 and K55.....	20
7.5.2	Grades N80 all Types, R95, L80, C90, T95 and P110.....	20
7.5.3	Grades C110 and Q125.....	21
7.5.4	Test specimen.....	21
7.5.5	Testing conditions.....	22
7.6	Charpy V-notch — Absorbed energy requirements for accessory material.....	22
7.6.1	Accessory material — General.....	22
7.6.2	Accessory material for accessories with internal API threads except integral tubing connections.....	22
7.6.3	Accessory material for accessories with internal special end-finish tapered interference-type threads.....	22
7.6.4	Accessory material for accessories with external threads.....	22
7.6.5	Accessory material for accessories with either integral tubing connections or internal special end-finish connections that do not have thread interference.....	22
7.6.6	Critical thickness for accessory material and special end-finish material.....	22
7.7	Maximum hardness.....	23
7.7.1	Grades L80 all types, C90, T95 and C110.....	23
7.7.2	Grade Q125 — All products.....	23
7.8	Hardness variation — Grades C90, T95, C110 and Q125.....	23
7.9	Process control — Grades C90, T95, C110 and Q125.....	23
7.10	Hardenability — Minimum percentage martensite for quenched and tempered products.....	24
7.10.1	Grade L80 Type 1.....	24
7.10.2	Grades C90 and T95.....	24
7.10.3	Grade C110.....	24
7.10.4	All grades except Grades L80, C90, T95 and C110.....	24
7.11	Grain size — Grades C90, T95 and C110.....	25
7.12	Surface condition — Grade L80 13Cr.....	25
7.13	Flattening — Electric-welded pipe.....	25
7.14	Sulfide stress cracking test — Grades C90, T95 and C110.....	25
7.14.1	General guidance.....	25
7.14.2	Test and retest requirements and recommendations.....	25
7.14.3	Test sample selection and location.....	26
7.14.4	Test solution.....	26
7.14.5	Minimum SSC requirements.....	27
7.14.6	Invalidation of tests.....	28
7.14.7	Additional testing provisions for ANSI/NACE TM0177-2016 Method D.....	28
<b>8</b>	<b>Dimensions, masses, tolerances, product ends and defects.....</b>	<b>28</b>
8.1	Labels and sizes.....	28
8.2	Dimensions and masses.....	28
8.3	Diameter.....	29
8.3.1	Measurement and design.....	29
8.3.2	Requirements.....	29
8.4	Wall thickness.....	29
8.5	Mass.....	29
8.6	Length.....	30
8.7	Casing jointers.....	30
8.8	Height and trim of electric-weld flash.....	30
8.8.1	Trimming electric-weld flash.....	30
8.8.2	Grades H40, J55, K55, N80 all types, R95; and L80 Type 1.....	30
8.8.3	Grades P110 and Q125.....	31
8.8.4	Disposition.....	31
8.9	Straightness.....	31

8.9.1	Pipe	31
8.9.2	Coupling stock, coupling material and accessory material	31
8.10	Drift requirements	31
8.11	Tolerances on dimensions and masses	32
8.11.1	Outside diameter	32
8.11.2	Wall thickness	32
8.11.3	Mass	32
8.11.4	Inside diameter	33
8.11.5	Upset dimensions	33
8.11.6	Extended length upsets	33
8.12	Product ends	33
8.12.1	Plain-end pipe	33
8.12.2	Product with API threads	33
8.12.3	Rounded nose	33
8.12.4	Threading	33
8.12.5	Special end finish	34
8.13	Defects	34
8.13.1	Pipe and accessory made from pipe	34
8.13.2	Accessory material not made from pipe, coupling stock and coupling material	34
8.13.3	Process control plan	35
8.14	Coupling make-up and thread protection	35
8.14.1	All Grades except Q125	35
8.14.2	Grade Q125	35
<b>9</b>	<b>Couplings</b>	<b>35</b>
9.1	General requirements	35
9.2	Alternative grades or heat treatments	36
9.3	Mechanical properties	36
9.4	Dimensions and tolerances	36
9.4.1	All Grades except Q125	36
9.4.2	Grade Q125	37
9.5	Regular couplings	37
9.6	Special-clearance couplings — All Grades except Q125	37
9.7	Combination couplings	37
9.8	Seal-ring couplings	37
9.9	Special-bevel tubing regular couplings — All Grades	37
9.10	Threading — Couplings	38
9.11	Surface inspection	38
9.12	Measurement of imperfections	38
9.13	Repair and removal of imperfections and defects	39
9.14	Thread surface treatment — Grade Q125	39
9.15	Couplings and coupling blank protection — Grades C90, T95, C110 and Q125	39
<b>10</b>	<b>Inspection and testing</b>	<b>39</b>
10.1	Test equipment	39
10.2	Lot definition for testing of mechanical properties	39
10.2.1	Grades H40, J55, K55, N80 all types, L80 Type 1, R95 and P110 — Coupling stock, coupling material and pipe (except pup joints heat-treated after cutting to blank or individual length)	39
10.2.2	Grades L80 13Cr, C90, T95, C110 and Q125 — Coupling stock, coupling material and pipe (except pup joints heat-treated after cutting to blank or individual length)	39
10.2.3	Coupling blanks, pup joints or accessory material heat-treated after cutting to blank or individual length	40
10.3	Testing of chemical composition	40
10.3.1	Heat analyses	40
10.3.2	Product analyses	40
10.3.3	Test method	40
10.3.4	Recheck of product analyses — All Grades	41

10.4	Tensile tests .....	41
10.4.1	Stress-relief temperature — All grades .....	41
10.4.2	Heat-control tensile tests — All Grades except Q125 .....	41
10.4.3	Frequency of testing and location of test specimen — Casing and tubing .....	41
10.4.4	Frequency of testing and test specimen location — Coupling stock, coupling material, coupling blanks, pup joints and accessory material .....	41
10.4.5	Test specimens — General .....	42
10.4.6	Test specimens — Additional requirements for coupling blanks, coupling stock coupling material and pup joint and accessory materials — Grades C110 and Q125 .....	42
10.4.7	Test method .....	42
10.4.8	Invalidation of tests .....	43
10.4.9	Retests — All products (except coupling blanks, coupling stock, coupling material, pup joints or accessory material) — Grades C90, T95, C110 and Q125 .....	43
10.4.10	Retests — Coupling blanks, coupling stock, coupling material, pup joints or accessory material in Grades C90, T95, C110 and Q125 .....	43
10.5	Flattening test .....	43
10.5.1	General requirement for testing .....	43
10.5.2	Frequency of testing .....	43
10.5.3	Test specimens .....	44
10.5.4	Test method for Grades H40, J55, K55, N80 all types, R95, and L80 Type 1 .....	44
10.5.5	Test method for Grade P110 pipe and Grade Q125 casing .....	44
10.5.6	Invalidation of tests .....	44
10.5.7	Retests .....	44
10.6	Hardness test .....	44
10.6.1	Frequency of testing — General .....	44
10.6.2	Frequency of testing — Heat-control tests — Grade L80 .....	45
10.6.3	Frequency of testing — Grade L80 .....	45
10.6.4	Frequency of testing and test specimen location — Non-upset pipe — Grades C90, T95 and C110 .....	45
10.6.5	Frequency of testing and test specimen location — Upset pipe — Grades C90 and T95 .....	45
10.6.6	Frequency of testing and test specimen location — Coupling blanks, coupling stock, coupling material, pup joints and accessory material — Grades C90, T95 and C110 .....	45
10.6.7	Frequency of testing — Grade Q125 .....	46
10.6.8	Test specimens .....	46
10.6.9	Test method .....	46
10.6.10	Invalidation of tests .....	48
10.6.11	Periodic checks of hardness-testing machines .....	48
10.6.12	Verification of hardness-testing machines and indenters .....	48
10.6.13	Retests — Grade L80 .....	49
10.6.14	Retests — Grades C90, T95 and C110 products except for coupling blanks, pup joints or accessory material heat-treated after cutting to individual lengths .....	49
10.6.15	Retests — Grades C90, T95 and C110 coupling blanks, pup joints or accessory material heat-treated after cutting to individual lengths .....	50
10.6.16	Retests — Grade Q125 — General .....	50
10.6.17	Retests — Grade Q125 — Casing, coupling stock and coupling material .....	50
10.6.18	Retests — Grade Q125 — Coupling blanks, pup joints and accessory material .....	50
10.6.19	Rejected lots — Grades L80 all types, C90, T95, C110 and Q125 .....	50
10.7	Impact test .....	50
10.7.1	Sampling — Grades J55 and K55 .....	50
10.7.2	Sampling — Grades N80 all types, R95, L80, C90, T95, C110 and P110 .....	50
10.7.3	Sampling and test specimen location — Grade Q125 .....	51
10.7.4	Test specimens .....	51
10.7.5	Test method .....	51

10.7.6	Invalidation of tests.....	51
10.7.7	Retest of a length — All Grades.....	51
10.7.8	Replacement of a reject length — All Grades.....	52
10.7.9	Multiple length rejection — Grade Q125.....	52
10.8	Grain size determination — Grades C90, T95 and C110.....	52
10.8.1	Sampling.....	52
10.8.2	Test method.....	52
10.9	Hardenability — Grades C90, T95 and C110.....	52
10.10	Sulfide stress-cracking test — Grades C90, T95 and C110.....	52
10.11	Metallographic evaluation — All EW Grades.....	52
10.12	Hydrostatic tests.....	53
10.12.1	Hydrostatic test procedures.....	53
10.12.2	Hydrostatic test requirements.....	53
10.12.3	Test pressure calculation.....	54
10.13	Dimensional testing.....	55
10.13.1	General.....	55
10.13.2	Diameter measurement.....	55
10.13.3	Diameter retests.....	55
10.13.4	Wall thickness measurement.....	56
10.13.5	Drift test.....	56
10.13.6	Length measurement.....	56
10.13.7	Mass (weight) determination.....	56
10.13.8	Straightness evaluation.....	57
10.13.9	Internal upset inspection.....	57
10.14	Visual inspection.....	57
10.14.1	General.....	57
10.14.2	Pipe body, coupling stock and coupling material (excluding pipe ends).....	58
10.14.3	Pipe ends.....	58
10.14.4	Disposition.....	58
10.15	Non-destructive examination (NDE).....	58
10.15.1	General.....	58
10.15.2	NDE personnel.....	59
10.15.3	Reference standards.....	59
10.15.4	NDE system capability records.....	59
10.15.5	Pipe body or coupling stock inspection — General.....	60
10.15.6	Full-body, full-length NDE of casing and tubing — Grades H40, J55, K55, N80 all types, L80 and R95.....	60
10.15.7	Full-body, full-length NDE of casing and tubing — Grade P110 to A.8 SR16.....	60
10.15.8	Full-body, full-length NDE of casing and tubing — Grade P110 and Grade P110 to A.8 SR16 and A.2 SR2.....	61
10.15.9	Full-body, full-length NDE of casing and tubing — Grades L80 13Cr, C90, T95, C110 and Q125.....	61
10.15.10	.....	
	NDE of the weld seam of welded pipe.....	61
10.15.11	.....	
	NDE of coupling stock, accessory material (except Grades L80 13Cr, C90, T95, C110 and Q125) and pup joints.....	62
10.15.12	.....	
	NDE of coupling stock and accessory material – Grades L80 13Cr, C90, T95, C110 and Q125.....	62
10.15.13	.....	
	NDE of coupling stock and accessory material — Grades C90 and T95.....	63
10.15.14	.....	
	Untested pipe ends, coupling stock ends and accessory material ends.....	64
10.15.15	.....	
	Pipe upsets.....	64
10.15.16	.....	
	Pipe, coupling stock and accessory material requiring further evaluation.....	64

10.15.17	.....	65
	Evaluation of indications (prove-up) .....	65
10.15.18	.....	65
	Disposition of pipe containing defects .....	65
10.15.19	.....	66
	Disposition of coupling stock and accessory material containing defects .....	66
<b>11</b>	<b>Marking</b> .....	<b>67</b>
11.1	General .....	67
11.2	Stamp marking requirements .....	68
11.2.1	Methods .....	68
11.2.2	Size .....	68
11.2.3	Location .....	68
11.2.4	Grades H40, J55, K55, N80 all types and P110 .....	68
11.2.5	Grades R95, L80 all types, C90, T95, C110 and Q125 .....	68
11.2.6	Make-up triangle marking .....	69
11.3	Stencil marking requirements .....	69
11.4	Colour identification .....	69
11.4.1	Colour coding .....	69
11.4.2	Product 1,8 m (6 ft) and longer .....	69
11.4.3	Loose couplings .....	70
11.4.4	Special-clearance couplings .....	70
11.4.5	Pup joints shorter than 1,8 m (6 ft) in length .....	70
11.4.6	Grade colour-codes .....	70
11.5	Thread and end-finish marking .....	70
11.5.1	API thread marking .....	70
11.5.2	Plain-end and special end-finish markings .....	70
11.6	Pipe-threader marking requirements .....	70
<b>12</b>	<b>Coating and protection</b> .....	<b>71</b>
12.1	Coatings .....	71
12.1.1	Coatings for protection during transit .....	71
12.1.2	Coatings for long-term storage .....	71
12.2	Thread protectors .....	72
12.2.1	General .....	72
12.2.2	Grade L80 13Cr .....	72
12.2.3	Driftable thread protectors .....	72
<b>13</b>	<b>Documents</b> .....	<b>72</b>
13.1	Electronic media .....	72
13.2	Certification requirements .....	72
13.3	Content of the certificate .....	72
13.4	Retention of records .....	74
<b>14</b>	<b>Minimum facility requirements for various categories of manufacturer</b> .....	<b>74</b>
14.1	Pipe mill .....	74
14.2	Processor .....	74
14.3	Pipe threader .....	74
14.4	Coupling, pup-joint or accessory manufacturer .....	75
<b>Annex A</b>	<b>(normative) Supplementary requirements</b> .....	<b>76</b>
<b>Annex B</b>	<b>(normative) Purchaser inspection</b> .....	<b>91</b>
<b>Annex C</b>	<b>(normative) Tables in SI units</b> .....	<b>92</b>
<b>Annex D</b>	<b>(normative) Figures in SI (USC) units</b> .....	<b>159</b>
<b>Annex E</b>	<b>(normative) Tables in USC units</b> .....	<b>182</b>
<b>Annex F</b>	<b>(informative) Procedures used to convert from USC units to SI units</b> .....	<b>248</b>
<b>Annex G</b>	<b>(normative) Requirements for thread protector design validation</b> .....	<b>260</b>

**Annex H (normative) High collapse requirements**..... 265  
**Bibliography**..... 267