

ISO 1431-1:2012-08 (E)

Rubber, vulcanized or thermoplastic - Resistance to ozone cracking - Part 1: Static and dynamic strain testing

Contents	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Principle	2
5 Apparatus (see Figure 1)	2
5.1 Test chamber	2
5.2 Source of ozonized air	3
5.3 Means of adjusting the ozone concentration	4
5.4 Means of determining the ozone concentration	4
5.5 Means of adjusting the gas flow	4
5.6 Mounting test pieces for static strain testing	4
5.7 Mounting test pieces for dynamic strain testing	5
6 Calibration	5
7 Test pieces	5
7.1 General	5
7.2 Wide test piece	6
7.3 Narrow test piece	6
8 Conditioning	6
8.1 Conditioning in the unstrained state	6
8.2 Conditioning in the strained state (for static strain testing only)	7
9 Test conditions	7
9.1 Ozone concentration	7
9.2 Temperature	7
9.3 Relative humidity	8
9.4 Maximum elongation	8
10 Static strain testing	8
10.1 General	8
10.2 Procedure A	8
10.3 Procedure B	8
10.4 Procedure C	8
11 Dynamic strain testing	9
11.1 General	9
11.2 Continuous dynamic exposure	9
11.3 Intermittent dynamic exposure	9
12 Expression of results	10
12.1 Procedure A	10
12.2 Procedure B	10
12.3 Procedure C (for static tests only)	10

13	Test report	11
	Annex A (informative) Ozone cracking -- Explanatory notes	13
	Annex B (normative) Calibration schedule	14
	Annex C (informative) Ozone cracking -- Rating scales	16
	Bibliography	17