

DIN EN 755-1:2016-10 (E)

Aluminium and aluminium alloys - Extruded rod/bar, tube and profiles - Part 1: Technical conditions for inspection and delivery

Contents

Page

European foreword	4
1 Scope	5
2 Normative references	5
3 Terms and definitions	6
4 Ordering information	6
5 Requirements	8
5.1 Production and manufacturing processes	8
5.2 Quality control	8
5.3 Chemical composition limits	8
5.4 Mechanical properties	8
5.5 Freedom from surface defects	9
5.6 Tolerances on dimensions and form	9
5.7 Stress corrosion cracking resistance	9
5.8 Additional requirements	9
6 Test procedures	9
6.1 Sampling	9
6.1.1 Samples for chemical analysis	9
6.1.2 Specimens for mechanical testing	10
6.1.3 Test pieces for tensile test	11
6.2 Test methods	11
6.2.1 Chemical composition limits	11
6.2.2 Tensile testing	11
6.2.3 Brinell hardness testing	11
6.2.4 Measurement of dimensions	11
6.2.5 Surface finish	12
6.2.6 Resistance to stress corrosion cracking	12
6.2.7 Additional tests	12
6.3 Re-tests	12
6.3.1 Chemical composition limits	12
6.3.2 Mechanical properties	12
6.3.3 Other properties	13
7 Inspection documents	13
8 Marking of products	13
9 Packaging	13
10 Arbitration	13
Annex A (normative) Location of test pieces	14
A.1 Round, square and hexagonal bar	14
A.1.1 For diameter (D) or width across flats (S) up to and including 40 mm	14
A.1.2 For diameter (D) or width across flats (S) over 40 mm	14

A.2	Rectangular bar	15
A.2.1	For thickness up to and including 12,5 mm	15
A.2.2	For thickness (T) over 12,5 mm and up to and including 40 mm	15
A.2.3	For thickness (T) exceeding 40 mm	15
A.3	Tube	16
A.4	Profiles	16
A.4.1	For thickness up to and including 12,5 mm	16
A.4.2	For thickness over 12,5 mm and up to and including 40 mm	16
A.4.3	For thickness exceeding 40 mm	17
 Annex B (normative) Resistance to stress-corrosion cracking for alloy EN AW-7075 in tempers		
	T73, T73510 and T73511 - Electrical conductivity	18
 Bibliography		19