

DIN EN 1254-6:2021-10 (E)

Copper and copper alloys - Plumbing fittings - Part 6: Push-fit fittings for use with metallic tubes, plastics and multilayer pipes

Contents	Page
European foreword	4
Introduction	5
1 Scope	6
2 Normative references	6
3 Terms and definitions	8
4 Product characteristics	8
4.1 Internal pressure	8
4.2 Tightness	8
4.3 Resistance to high temperature (for heating networks)	9
4.4 Release of dangerous substances	9
4.5 Durability	10
4.6 Wall thickness at threaded portions of adaptor fittings	10
4.7 Dimensions of tail pipe ends for swivel fittings	10
4.8 Threaded end dimensions	11
4.9 Other adapter ends (not defined in EN 1254-20:2021)	11
4.10 Bore dimensions	11
4.11 Identity of elastomeric sealing material	11
4.12 Tube / pipe abutment	11
4.13 Alignment of the fitting ends	11
4.14 Shapes for tightening systems	12
4.15 Surface condition	12
4.16 Disconnection and re-use (for fittings capable of being disconnected)	12
4.17 Plated or coated surfaces	12
5 Testing, assessment and sampling methods	12
5.1 General	12
5.2 Internal hydrostatic pressure test	12
5.3 Tightness	13
5.4 Durability	16
5.5 Wall thickness at threaded portions of adaptor fittings	17
5.6 Dimensions of tail pipe ends for swivel fittings	18
5.7 Threaded end dimensions	18
5.8 Bore dimensions	18
5.9 Identity of elastomeric sealing material for liquid applications	18
5.10 Alignment of the fitting ends	18
5.11 Disconnection and re-use (for fittings capable of being disconnected)	18
6 Evaluation of conformity	19
6.1 General	19
6.2 Type testing	19
6.3 Test reports	22
6.4 Factory production control (FPC)	22
7 Designation	25
8 Marking, labelling and packaging	25

8.1	General	25
8.2	Dezincification resistant copper zinc alloys	25
Annex A (normative) Operating temperatures and design pressures		26
Bibliography		28