DIN EN 14034-2:2006-08 (E)

Determination of explosion characteristics of dust clouds - Part 2: Determination of the maximum rate of explosion pressure rise (dp/dt)<(Index)max> of dust clouds

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 6

4 Test apparatus 7
4.1 General 7
4.2 Explosion vessel 7
4.3 Dust dispersion system (dust container, fast acting valve, connecting tube, dust disperser) 8
4.4 Ignition source 10
4.5 Control unit 11
4.6 Pressure measuring system 11

5 Dust sample 11

6 Test procedure 11

7 Calibration and verification 14
7.1 Calibration 14
7.2 Verification 14

8 Safety precautions / instructions 15

9 Alternative test equipment / procedures 15

10 Test report 16

Annex A (normative) Electro Pneumatic Valve 17

Annex B (normative) Dust dispenser with 5 mm holes 19

Annex C (normative) 20 l sphere 22

C.1 General 22
C.2 Test apparatus 22
C.3 Test conditions 23
C.4 Test procedure 23
C.5 Calculation of (dp/dt)max, 20 l, Kmax and KSt 24

Annex ZA (informative) Relationship between this European Standard and the Essential Requirements of EU Directive 94/9/EC 25

Bibliography 26

Figures Figure 1 -- 1 m³ vessel (schematic) 8

Figure 2 -- Dust container with blasting cap activated valve as commonly used for explosion suppression (schematic; it is commercially available) 9

Figure 3 -- Location of the 6 mm holes in the dust disperser 10

Figure 4 -- Dust dispersion and pressure-time curve 13

Figure 5 -- Determination of the maximum rate of explosion pressure rise (dp/dt)max 14

Figure A.1 -- Electro Pneumatic Valve (schematic) 17

Figure A.2 -- Discharge characteristic of dust dispersers (without dust) 18

Figure B.1 -- Location of the 5 mm holes in the dust disperser 20

Figure B.2 -- Rebound nozzle 21

Figure B.3 -- Dispersion cup 21

Figure C.1 -- Test equipment 20 l sphere (schematic) 23

Tables Table 1 -- Maximum permissible deviations SEQ 15

Table ZA.1 -- Correspondence between this European Standard and Directive 94/9/EC 25